



Turbocleaner N 20 on Ladog 1400

The Turbocleaner N 20 on Ladog 1400 is ideally suited to clean oil spots and tracks and for special cleaning of sports surfaces, construction site cleaning and gum removal* on traffic areas with up to 500 bar water pressure. The Turbocleaner is small, agile and used almost anywhere .

Specifications:

Ladog T1400

Euro 5 90 kw	Performance: 60 km/h
GVW:	6 000 kg
Wheelbase:	2 600 mm
Hydraulics for oil track cleaner	
Tires:	245/65R16

Turbocleaner:

Structure including cleaning unit completely in stainless steel
 Dirt container: 2 240 Liter
 Freshwater tank 1 420 Liter
 Container opened hydraulically

High performance centrifugal fan
 Power consumption max. 18 kW
 Suction hose DN 200

High pressure plunger pump
 Quantity 38 l/min
 Pressure 250 bar
 Power 18,2 kW
 Drive hydraulic

Surface Cleaner Turbocleaner 1500
 Hydraulic tilting right and left, about 400 mm
 Cleaning width: 1 500 mm
 extra large castors, diameter 200 mm
 for traversing edges

Hot water Therme 90 KW with flame monitoring
 Operating pressure: up to 300 bar
 Resources: Diesel, 12 V DC



*maximum working width for chewing gum removal: 600 mm